

1. *Unique identification code of the product-type:*  
**Calcium lime EN 459-1 CL 90-Q (R5, P1)**

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*  
**Ventilated calcium oxide - Date and site of production or other identification data are printed on the packaging and / or on the Transport Document**

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*  
**Used in applications or building materials, construction and civil engineering**

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*  
**FORNACI ZULIAN S.r.l.**  
**Via Caduti sul Lavoro, 11**  
**I-35014 Fontaniva (PD)**  
**Plant of Fontaniva (PD)**

Contacts:  
 Tel. +39.(0)49.5941023 - Fax: +39.(0)49.5942957  
 E-mail: [info@fornacizulian.it](mailto:info@fornacizulian.it)

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*  
**Not applicable**

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*  
**System 2+**

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*  
 Notified Body "SGS ICS Italia Srl" (notification n. 1381) performed according to the 2+ system:  
 i) initial inspection of the manufacturing plant and factory production control;  
 ii) continuous surveillance, assessment and verification of factory production control;  
 and issued the certificate of conformity of the factory production control:  
**n. 1381-CPR-255**

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:* **Not applicable**

9. *Declared performance:*

Essential characteristics	Performance	Harmonised standard
CaO + MgO	<b>≥ 90 %</b>	EN 459-1:2010
MgO	<b>≤ 5 % (see 4.4.2 in EN 459-1)</b>	
CO <sub>2</sub>	<b>≤ 4 % (see 4.4.2 in EN 459-1)</b>	
SO <sub>3</sub>	<b>≤ 2 %</b>	
Available lime	<b>≥ 80 %</b>	
Stability	<b>pass</b>	
Reactivity	<b>R5</b>	
Particle size distribution	<b>P1</b>	

10. *The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.*  
*This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.*

*Signed for and on behalf of the manufacturer by:*

**General Manager**  
**Dott. Simone Zulian**  
