

1. <i>Unique identification code of the product-type:</i> Calcium lime EN 459-1 CL 90-Q (R5, P1)		
2. <i>Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):</i> Ventilated calcium oxide - Date and site of production or other identification data are printed on the packaging and / or on the Transport Document		
3. <i>Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:</i> Used in applications or building materials, construction and civil engineering		
4. <i>Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):</i> FORNACI ZULIAN S.r.l. Via Caduti sul Lavoro, 11 I-35014 Fontaniva (PD) Plant of Fontaniva (PD) Contacts: Tel. +39.(0)49.5941023 - Fax: +39.(0)49.5942957 E-mail: info@fornacizulian.it		
5. <i>Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):</i> Not applicable		
6. <i>System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:</i> System 2+		
7. <i>In case of the declaration of performance concerning a construction product covered by a harmonised standard:</i> Notified Body "SGS Italia" (notification n. 1381) performed according to the 2+ system: i) initial inspection of the manufacturing plant and factory production control; ii) continuous surveillance, assessment and verification of factory production control; and issued the certificate of conformity of the factory production control: n. 1381-CPR-255		
8. <i>In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:</i> Not applicable		
9. <i>Declared performance:</i>		
Essential characteristics	Performance	Harmonised standard
CaO + MgO	≥ 90 %	EN 459-1:2010
MgO	≤ 5 % (see 4.4.2 in EN 459-1)	
CO ₂	≤ 4 % (see 4.4.2 in EN 459-1)	
SO ₃	≤ 2 %	
Available lime	≥ 80 %	
Stability	pass	
Reactivity	R5	
Particle size distribution	P1	
10. <i>The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.</i> <i>This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</i>		

Signed for and on behalf of the manufacturer by:

General Manager
Dott. Simone Zulian

